

High Flow EMERGENCY VENT

PATENT PENDING

C UL US Listed

High Flow Emergency Vent Flanged Style

High Flow Emergency Vent provides significant SCFH airflow relief when required.

Flanged style eliminates the potential for cross threading during installation.

Standard Features

UL US & Canada Listed

Buna N O Ring - provides vapor tight seal

Spring Actuated-assures accurate opening pressure

All Aluminum Construction-lightweight for easy handling and installation. Also, no rust issues from scratches or weathering

Pressure relief set at 0.5 PSI

Bolt pattern conforms to ANSI B16.5 specifications



370

Part #	Size	Weight/LBS
0370-09-6000	6"	14
0370-09-8000	8"	18
0370-09-1000	10"	22

SCFH Airflow at 2.5 PSI,	Standard Opening Pressure is 0.5 PSI	
0370-03-60HF 6"	0370-03-80HF 8"	0370-03-10HF 10"
Without Screen 251,700	507,198	715,724
With Screen 237,000	456,123	712,828

Accessories available include:

Mild Steel Adaptor - 6" #0370-09-6001; 8" #0370-09-8001, 10" #0370-09-1001
Available in 6" and Special Height of 12"

Bolts, Nuts & Gaskets
Screens

Warning-The emergency vent is designed for "emergency pressure relief" and must be used in conjunction with other venting devices. The emergency vent must be properly sized per UL requirements.

Clay & Bailey emergency vents comply with various codes -PEI RP200, Underwriters Laboratories of US and Canada UL-142, UL-2085, UL-2244, NFPA30, 30A, API 2000



6401 E. 40th St. Kansas City, Missouri 64129

1-816-924-3900 1-800-821-6583 FAX: 1-816-924-3903
www.claybailey.com email: CandBmfg@claybailey.com

Clay and Bailey Mfg. Co.

Flanged Adaptor

Available in
6", 8", 10" Sizes

Mild Steel Material
in 1/4" Thickness

