


Features

Heavy Duty Cast Iron Double Tapped Bushings for use on underground or aboveground storage tanks. Internal and external threads are true, for straight piping runs. NPT threads are standard.



120



Part No.	Size	lbs	Thds A	Thds B
0120-01-2037	2"	1.75	2"	3/8"
0120-01-2005	2"	1.5	2"	1/2"
0120-01-2075	2"	1.5	2"	3/4"
0120-01-2001	2"	1.25	2"	1"
0120-01-2012	2"	1.0	2"	1 1/4"
0120-01-2015	2"	1.0	2"	1 1/2"
0120-01-2051	2 1/2"	2.25	2 1/2"	1"
0120-01-2050	2 1/2"	2.25	2 1/2"	1 1/4"
0120-01-2059	2 1/2"	2.0	2 1/2"	1 1/2"
0120-01-2052	2 1/2"	2.0	2 1/2"	2"
0120-01-3001	3"	3.0	3"	1"
0120-01-3012	3"	2.75	3"	1 1/4"
0120-01-3015	3"	2.75	3"	1 1/2"
0120-01-3020	3"	2.5	3"	2"
0120-01-3025	3"	2.25	3"	2 1/2"
0120-01-3051	3 1/2"	4.0	3 1/2"	1"

Part No.	Size	lbs	Thds A	Thds B
0120-01-3050	3 1/2"	3.25	3 1/2"	1 1/2"
0120-01-3052	3 1/2"	3.0	3 1/2"	2"
0120-01-3059	3 1/2"	3.0	3 1/2"	2 1/2"
0120-01-3053	3 1/2"	3.0	3 1/2"	3"
0120-01-4001	4"	5.0	4"	1"
0120-01-4012	4"	4.75	4"	1 1/4"
0120-01-4015	4"	4.5	4"	1 1/2"
0120-01-4002	4"	3.5	4"	2"
0120-01-4025	4"	3.5	4"	2 1/2"
0120-01-4003	4"	4.75	4"	3"
0120-01-4035	4"	4.0	4"	3 1/2"
0120-01-5003	5"	8	5"	3"
0120-01-5004	5"	6	5"	4"
0120-01-6003	6"	12	6"	3"
0120-01-6004	6"	11	6"	4"