

EMERGENCY VENTS

NEW!



LISTED!



367

Features


Slimline style is ideal for limited space applications. Heavy duty cast iron top and base with aluminum bases available. Machined top and base with a Buna N "O" Ring provide a vapor tight seal. 4" or 6" male NPT thread standard. Screen minimizes chances of theft or vandalism.

Airflow:

	w/screen	wo/screen
4" -	91,076 SCFH	105,460 SCFH
5" -	171,300 SCFH	194,725 SCFH
6" -	227,191 SCFH	267,284 SCFH

Part No.	A NPT		B
	Size	Wt.lbs	
0367-01-4000	4"	17.0	4 11/16"
0367-01-5000	5"	22.0	5"
0367-01-6000	6"	26.0	5 1/8"
0367-03-4000*	4"	14.0	4 11/16"
0367-03-5000*	5"	20.0	5"
0367-03-6000*	6"	25.0	5 1/8"

*Aluminum Base



368

Features

Female thread, hood design made of heavy duty cast iron top and base with aluminum bases available. Hood design acts as a weather deflector and minimizes chances of theft or vandalism. Machined top & base with Buna N "O" Ring provides a vapor tight seal.

Airflow:

	w/screen	wo/screen
4" -	77,415 SCFH	89,641 SCFH
6" -	210,527 SCFH	227,988 SCFH
8" -	477,033 SCFH	553,507 SCFH

Part No.	A NPT		B
	Size	Wt.lbs	
0368-01-4000	4"	21.0	4 1/8"
0368-01-6000	6"	31.0	5"
0368-01-8000	8"	41.0	4 1/8"
0368-03-4000*	4"	19.0	4 1/8"
0368-03-6000*	6"	28.0	5"
0368-03-8000*	8"	37.0	4 1/8"

*Aluminum Base

