

EMERGENCY VENTS

NEW!



LISTED!



366

Emergency Vent Airflow Capacity Chart

SCFH=Standard Cubic Feet Per Hour @ 2.5 psig
Screens are standard 4 mesh galvanized steel.
Clay & Bailey emergency vents are flow tested and UL listed.

Size	Part No.	Capacity w/o Screen	Capacity w/Screen
2"	0354-02-2000	19,218	17,707
3"	0365-01-3000	46,983	43,770
3"	0365-03-3000	46,983	43,770
4"	0366-01-4000	105,46091,076	
4"	0367-01-4000	105,46091,076	
4"	0368-01-4000	89,641	77,415
4"	0369-01-4000	89,641	77,415
4"	0366-03-4000	105,46091,076	
4"	0367-03-4000	105,46091,076	
4"	0368-03-4000	89,641	77,415
4"	0369-03-4000	89,641	77,415
5"	0366-01-5000	194,725171,300	
5"	0366-03-5000	194,725171,300	
5"	0367-01-5000	194,725171,300	
5"	0367-03-5000	194,725171,300	
6"	0366-01-6000	267,284227,191	
6"	0367-01-6000	267,284227,191	
6"	0368-01-6000	227,988210,527	
6"	0369-01-6000	227,988210,527	
6"	0366-03-6000	267,284227,191	
6"	0367-03-6000	267,284227,191	
6"	0368-03-6000	227,988210,527	
6"	0369-03-6000	227,988210,527	
8"	0368-01-8000	553,507477,033	
8"	0369-01-8000	553,507477,033	
8"	0368-03-8000	553,507477,033	
8"	0369-03-8000	553,507477,033	
8"	0370-03-8000	518,821448,054	
10"	0370-01-1000	788,616672,108	

Part No.	A NPT Size	Wt.lbs	B
0366-01-4000	4"	17.6	5 3/16"
0366-01-5000	5"	22.0	5 3/4"
0366-01-6000	6"	27.6	6 1/4"
0366-03-4000*	4"	10.2	5 3/16"
0366-03-5000*	5"	20.0	5 3/4"
0366-03-6000*	6"	19.3	6 1/4"

*Aluminum Base

Features

Slimline style is ideal for limited space situations. Durable cast iron top and base with aluminum bases available. Machined top and base with a Buna N "O" Ring provide a vapor tight seal. Air flow at 2.5psi is 91,076 SCFH for 4" with screen and 227,191 SCFH for 6" with screen. 4", 5" or 6" NPT female thread is standard.

