



Part No.	P/V	Wt.lbs	Size
Brass			
0088-02-2000	3oz/3oz	7.0	2"
0088-02-2083	8oz/3oz	8.0	2"
0088-02-2040	16oz/3oz	11.0	2"
0088-02-3020	3oz/3oz	21.0	3"
Aluminum			
0088-03-2000	1oz/1oz	2.0	2"
0088-03-2030	3lb/1oz	2.0	2"
0088-03-3000	1oz/1oz	6.0	3"

Features

Storage tank vent valve seats are machined. Openings in the sides of the valve are covered with No. 40 mesh fire screen. Hoods protect vent openings from weather.



88



300

Part No.	A NPT Size	Wt.lbs	B	SCFH at 2.5 psi
0300-01-0750	3/4"	1.0	4"	4,894
0300-01-1000	1"	1.1	4 1/2"	8,711
0300-01-1250	1 1/4"	1.6	4 1/2"	13,616
0300-01-1500	1 1/2"	2.1	6"	19,532
0300-01-2000	2"	2.7	7 1/2"	34,846
0300-01-2500	2 1/2"	3.2	8 1/2"	53,067
0300-01-3000	3"	5.8	10"	78,350

Features

Heavy duty cast iron body. Double outlet free flow vent. Brass screen prevents contaminants from entering the tank. Available in 3/4" through 3" NPT female threads. Zinc plated finish and set screw style available. Also available in aluminum.