

# High Flow EMERGENCY VENT

**PATENT #8,171,955**

C  US Listed

## High Flow Emergency Vent Male Thread Style

Clay & Bailey's High Flow Emergency Vent provides significant SCFH airflow relief when required.

### Standard Features

UL US & Canada Listed

Buna N O Ring - provides vapor tight seal

Spring Actuated- assures accurate opening pressure

All Aluminum Construction- lightweight for easy handling and installation. Also, no rust issues from scratches or weathering

Pressure relief set at 0.5 PSI, Full open at 2.5PSI



**367 HIGH FLOW**

Part #	Size	Weight/LBS
0367-03-30HF	3"	3.0
0367-03-40HF	4"	4.0
0367-03-50HF	5"	5.0
0367-03-60HF	6"	6.0
0367-03-80HF	8"	7.0

### SCFH Airflow at 2.5 PSI

	0367-03-30HF	0367-03-40HF	0367-03-50HF	0367-03-60HF	0367-03-80HF
Without Screen	71,750	118,750	200,250	251,700	459,000
With Screen	66,400	114,800	184,500	237,000	430,500

Warning-The emergency vent is designed for "emergency pressure relief" and must be used in conjunction with other venting devices. The emergency vent must be properly sized per UL requirements.

Clay & Bailey emergency vents comply with various codes -PEI RP200, Underwriters Laboratories of US and Canada UL-142, UL-2085, UL-2244, NFPA30, 30A, API 2000

