

HIGH FLOW EMERGENCY VENT

PATENT # 8,171,955

C  US Listed

High Flow Emergency Vent Female Thread Style

Clay & Bailey's High Flow Emergency Vent provides significant SCFH airflow relief when required.

Standard Features

UL US & Canada Listed

Buna N O Ring - provides vapor tight seal

Spring Actuated-assures accurate opening pressure

All Aluminum Construction-lightweight for easy handling and installation. Also, no rust issues from scratches or weathering

Pressure relief set at 0.5 PSI, Full open at 2.5PSI



366 HIGH FLOW

Part #	Size	Weight/LBS
0366-03-30HF	3"	3.0
0366-03-40HF	4"	4.0
0366-03-50HF	5"	5.0
0366-03-60HF	6"	6.0
0366-03-80HF	8"	7.0

SCFH Airflow at 2.5 PSI

	0366-03-30HF	0366-03-40HF	0366-03-50HF	0366-03-60HF	0366-03-80HF
Without Screen	71,750	118,750	200,250	251,700	531,280
With Screen	66,400	114,800	184,500	237,000	500,552

Warning-The emergency vent is designed for "emergency pressure relief" and must be used in conjunction with other venting devices. The emergency vent must be properly sized per UL requirements.

Clay & Bailey emergency vents comply with various codes -PEI RP200, Underwriters Laboratories of US and Canada UL-142, UL-2085, UL-2244, NFPA30, 30A, API 2000

