

Clay & Bailey Mfg. Co.



A CENTURY'S WORTH OF INNOVATION

366 FEMALE EMERGENCY VENT FOR ABOVEGROUND STORAGE TANKS



Made in America



366 Slimline

Features:

Slimline style is ideal for limited space applications. Heavy duty cast iron top and base with aluminum bases available. Machined top and base with a Buna N "O" Ring provide a vapor tight seal. 4", 5" and 6" NPT female thread standard. Optional screen minimizes chances of theft or vandalism.

Clay & Bailey vents can be used in a variety of Aboveground Storage Tank Equipment installations where reliable fuel handling petroleum equipment is required.

Airflow:

w/screen	wo/screen
4" - 91,076 SCFH	105,460 SCFH
5" - 171,300 SCFH	194,725 SCFH
6" - 227,191 SCFH	267,284 SCFH

Part No	Size	Wt./Lbs.
0366-01-4000	4"	17.6
0366-01-5000	5"	22.0
0366-01-6000	6"	27.6

Clay & Bailey emergency vents comply with various codes – Petroleum Equipment Institute PEI RP200; Underwriters Laboratories Inc. UL-142, UL-2085, UL-2244, Underwriters Laboratories of Canada ULC-S601; National Fire Protection Agency NFPA30, NFPA30A; American Petroleum Institute API 2000.

