

# Clay & Bailey Mfg. Co.



A CENTURY'S WORTH OF INNOVATION

## 367 MALE EMERGENCY VENT FOR ABOVEGROUND STORAGE TANKS



Made in America



**367 Slimline**

### Features:

Slimline style is ideal for limited space applications. Heavy duty cast iron top and base with aluminum bases available. Machined top and base with a Buna N "O" Ring provide a vapor tight seal. 4", 5" and 6" male NPT thread standard. Optional screen minimizes chances of theft or vandalism.

Clay & Bailey vents can be used in a variety of Aboveground Storage Tank Equipment installations where reliable fuel handling petroleum equipment is required.

### Airflow:

	w/screen		wo/screen	
3"-	43,770 SCFH		46,983	SCFH
4" -	91,076 SCFH		105,460	SCFH
5" -	171,300 SCFH		194,725	SCFH
6" -	227,191 SCFH		267,284	SCFH

Part No.	Size	Wt./Lbs.
0365-01-3000	3"	10.0
0367-01-4000	4"	17.0
0367-01-5000	5"	22.0
0367-01-6000	6"	26.0

Clay & Bailey emergency vents comply with various codes - PEI RP200, ULC-S601, UL-142. UL-2085, UL-2244, NFPA30, 30A and API 2000.

