

Clay & Bailey Mfg. Co.



A CENTURY'S WORTH OF INNOVATION

367 MALE EMERGENCY VENT FOR ABOVEGROUND STORAGE TANKS



Made in America



367 Slimline

Features:

Slimline style is ideal for limited space applications. Heavy duty cast iron top and base with aluminum bases available. Machined top and base with a Buna N "O" Ring provide a vapor tight seal. 4", 5" and 6" male NPT thread standard. Optional screen minimizes chances of theft or vandalism.

Clay & Bailey vents can be used in a variety of Aboveground Storage Tank Equipment installations where reliable fuel handling petroleum equipment is required.

Airflow:

	<u>w/screen</u>		<u>wo/screen</u>	
3"-	43,770	SCFH	46,983	SCFH
4" -	91,076	SCFH	105,460	SCFH
5" -	171,300	SCFH	194,725	SCFH
6" -	227,191	SCFH	267,284	SCFH

<u>Part No.</u>	<u>Size</u>	<u>Wt./Lbs.</u>
0365-01-3000	3"	10.0
0367-01-4000	4"	17.0
0367-01-5000	5"	22.0
0367-01-6000	6"	26.0

Clay & Bailey emergency vents comply with various codes - Petroleum Equipment Institute PEI RP200; Underwriters Laboratories Inc. UL-142, UL-2085, UL-2244, Underwriters Laboratories of Canada ULC-S601; National Fire Protection Agency NFPA30, NFPA30A; American Petroleum Institute API 2000.

