

366 Female Emergency Vent For Aboveground Storage Tanks



366

Features:

Slim line style is ideal for limited space applications. Heavy-duty cast-iron top and base with aluminum bases available. Machined top and base with Buna-N O Ring provide a vapor resistant seal. 4", 5", and 6" female NPT thread standard. Optional screen minimizes chances of theft or vandalism.

Clay & Bailey vents can be used in a variety of Aboveground Storage Tank Equipment installations where reliable fuel handling petroleum equipment is

Airflow

| Part # | Size | Weight/Lbs. | Airflow | |
|--------------|------|-------------|-------------|--------------|
| | | | Size | W/O Screen |
| 0366-01-4000 | 4" | 18 | 4" W/Screen | 105,460 SCFH |
| 0366-01-5000 | 5" | 22 | 5" W/Screen | 194,725 SCFH |
| 0366-01-6000 | 6" | 28 | 6" W/Screen | 267,284 SCFH |



Clay & Bailey emergency vents comply with various codes – Petroleum Equipment Institute PEI RP200; Underwriters Laboratories Inc. UL-142, UL-2085, UL- 2244, Underwriters Laboratories of Canada ULC-S601; National Fire Protection Agency NFPA 30, NFPA 30A; American Petroleum Institute API 2000.



10/2018