

367 Male Thread High Flow Emergency Vent for Aboveground Storage Tanks



367 HF

Features:

All Aluminum Construction is lightweight for easy handling and installation. Also, no rust issues from scratches or weathering. Buna-N O Ring provides a vapor resistant seal. Spring Actuated Vent assures accurate opening pressure. Pressure relief set at <0.5 PSI. Clay & Bailey vents can be used in a variety of Aboveground Storage Tank Equipment installations where reliable fuel handling petroleum equipment is required.

Airflow

<u>Part #</u>	<u>Size</u>	<u>Weight /lbs.</u>	<u>Size</u>	<u>W/Screen</u>	<u>W/O Screen</u>
0367-03-30HF	3"	3	3"	66,400 SCFH	71,750 SCFH
0367-03-40HF	4"	4	4"	114,800 SCFH	118,750 SCFH
0367-03-50HF	5"	5	5"	184,500 SCFH	200,250 SCFH
0367-03-60HF	6"	6	6"	237,000 SCFH	251,700 SCFH
0367-03-80HF	8"	7	8"	500,552 SCFH	556,539 SCFH



Clay & Bailey emergency vents comply with various codes – Petroleum Equipment Institute PEI RP200; Underwriters Laboratories Inc. UL-142, UL-2085, UL-2244, UL-2583; Underwriters Laboratories of Canada ULC-S601; National Fire Protection Agency NFPA 30, NFPA 30A; American Petroleum Institute API 2000.



10/2018