

# Clay & Bailey Mfg. Co.



A CENTURY'S WORTH OF INNOVATION

## 01228 3" NICKEL PLATED OP VALVE FOR ABOVEGROUND STORAGE TANKS



**#1228 C&B 3 X 4**

U.S. Patent #5,531,247

## Features

The nickel plated OP Valves are used with alternative fuels such as Methanol, Ethanol, E-85 and Bio-diesel. Designed for AST's requiring high GPM flow rate, but only having a 4" NPT opening. The C&B 3x4 has a 3" fill and easily installs in a 4" opening. Flow rate is over 300 gallons per minute at 40 psi. The C&B 3X4 is rated for fuel delivery up to 100 psi and provides positive fuel shut off at high fill rates. Entirely mechanical in operation, the C&B 3X4 can be used in remote fill applications, retrofitted to an existing AST, and has a unique drain back system designed to allow the delivery hose to be emptied after fuel delivery has been stopped. The 3" NPT fill opening allows easy connection to piping or cam fittings. Clay & Bailey Overfill Prevention Valves can be used in a variety of Aboveground Storage Tank Equipment installations where reliable fuel handling petroleum equipment is required.

### C&B 3 X 4 Options

Part No.	Description
----------	-------------

1228-17-3053	3" Cam Lock Adaptor
--------------	---------------------

1228-03-3054	3" Cam Lock Dust Cap
--------------	----------------------

See C&B 2 X 4 Options for drop tubes

\*Applicable for fuels other than #5 and #6 fuel oils. Consult factory for special applications.

Part No.	Size	Wt.lbs
----------	------	--------

### Standard Fill Tube Sizes

1228-17-3510	10"
1228-17-3516	16"
1228-17-3520	20"
1228-17-3524	24"



Clay & Bailey Overfill Prevention Valves comply with PEI RP200, RP600, UFC, IFC and Florida DEQ.