

Clay & Bailey Mfg. Co.



A CENTURY'S WORTH OF INNOVATION

01228 2" NICKEL PLATED OP VALVE FOR ABOVEGROUND STORAGE TANKS



#1228 C&B 2 X 4

U.S. Patent #5,531,247

Features

The nickel plated OP Valves are used with alternative fuels such as Methanol, Ethanol, E-85 and Bio-diesel. Designed for AST's requiring high GPM flow rate, but only having a 4" NPT opening. The C&B 2x4 has a 2" fill and easily installs in a 4" opening. Flow rate is over 200 gallons per minute at 40 psi. The C&B 2X4 is rated for fuel delivery up to 100 psi and provides positive fuel shut off at high fill rates. Entirely mechanical in operation, the C&B 2X4 can be used in remote fill applications, retrofitted to an existing AST, and has a unique drain back system designed to allow the delivery hose to be emptied after fuel delivery has been stopped. The 2" NPT fill opening allows easy connection to piping or cam fittings. Clay & Bailey Overfill Prevention Valves can be used in a variety of Aboveground Storage Tank Equipment installations where reliable fuel handling petroleum equipment is required.

C&B 2 X 4 Options

Part No.	Description
----------	-------------

1228-17-2053	2" Cam Lock Adaptor
1228-03-2054	2" Cam Lock Dust Cap

See C&B 2 X 4 Options for drop tubes

Part No.	Size	Wt.lbs
----------	------	--------

Standard Fill Tube Sizes

Part No.	Length
1228-17-2010	10"
1228-17-2016	16"
1228-17-2020	20"
1228-17-2024	24"

Clay & Bailey Overfill Prevention Valves comply with PEI RP200, RP600, UFC, IFC and Florida DEQ.

